



S2100 Series 2n1 Features & Benefits

- Integrated symmetric/asymmetric design delivers two choices for optimum vehicle lifting.
- Three-stage telescopic front arms for maximum reach and vehicle coverage.
- Adjustable height and width options accommodate varying service bay sizes.
- Double Telescopic Screw Pads adjust to multiple heights minimizing the need for adapters.
- Single point safety lock release and two hand lift lowering for fast and safe operation.
- Padded overhead shut off system prevents vehicle damage from being raised too high.
- 48" elongated carriage design decreases load on bearing
- Stack pad lifting system adapts to both cars and trucks without the need for extra adapters.
- Available 2' extended column enables technician to work at an ergonomic height when servicing taller vehicles.

NEW & Improved S-Series

The New and Improved Ammco S-Series 2n1 lift features three-stage telescopic front arms, adjustable height and width options, wide rubber door guards and a padded overhead shut off bar just to name a few. It hoists a hefty 10,000 lbs. of passenger car, light truck or SUV while providing a clear floor for unimpeded motion.

2n1 Asymmetrical/Symmetrical Design

The Ammco S-Series 2n1 Lift gives you the option of selecting either asymmetrical or symmetrical lifting depending on the vehicle you're servicing. The S-Series also provides a wide, open workspace for mobile shop equipment and personnel.

Column Height

The S-Series lift has an 11' 8" standard height that allows it to be placed in a standard service bay with a 12' ceiling.

Stack Pad Lifting System

The sure grip multi-surface stack pads adapt to car or truck pickup points without the need for extra adapters. The S-Series comes standard with four 3" stacks, two 6" stacks and two organizer racks that mount to the lift columns.

Truck Adapter Kit Included



	4S21NSR1 (red) 4S21NSB1 (blue)	4S21NSR3 (red) 4S21NSB3 (blue)	4S21NXR1 (red) 4S21NXB1 (blue)	4S21NXR3 (red) 4S21NXB3 (blue)
Maximum Lifting Capacity*	10,000 lb. (4536kg)			
Rise Height ¹	74 ⁵ / ₈ " (1895mm)			
Column Height (min/max)	11'8" (3556mm)		13'8" (4166mm)	
Cylinder Overall (Full Stroke)	11'11" (3632mm)			
Adj. Overall Width (min/max)	11'6 ¹ / ₂ " / 11'11" (3518mm / 3632mm)			
Drive-thru Clearance (min/max)	100 ¹ / ₂ " / 105" (2553mm / 2667mm)			
Floor to Overhead Switch (min/max)	11'2 ¹ / ₂ "(3416mm)		13'2 ¹ / ₂ (4026mm)	
Front Arm Reach (min/max)	27" / 41" (686mm / 1041mm)			
Rear Arm Reach (min/max)	42 / 59" (1067mm / 1499mm)			
Screw Pad Height (min/max) ²	4 ¹ / ₈ "-6 ⁵ / ₈ " (105mm-168mm)			
Inside of Columns (min/max)	110" / 114 ¹ / ₂ " (2794mm / 2908mm)			
Ceiling Height Required ³ (min/max)	12' (658mm)		13'9" (4191mm)	
Motor	2HP, Single Phase, 60Hz	2HP, Three Phase, 60Hz	2HP, Single Phase, 60Hz	2HP, Three Phase, 60Hz
Voltage	208 - 230v	208 or 220-240v (specify at time of order)	208 - 230v	208 or 220-240v (specify at time of order)
Speed of Rise	48 seconds			
Max. Load Per Arm	2,500 lb. (1134kg)			

Specifications subject to change without notice.

*Lift capacity ratings are based on loads equally distributed on all four arms.

¹ Rise height is measured with superstructure in highest position.

² Specifications are listed without rubber pad, for measurements with rubber pad add 1/4" (6mm).

³ Ceiling height requirement may exceed 12' or 13' 9" if column shimming is necessary..

Accessories



4S00896

Air / Electric Tool Station to supply lift with an air and electric supply.

HENNESSY INDUSTRIES, INC.

Manufacturer of Ammco®, Coats® and BADA® Automobile Service Equipment, Tools and Accessories.

1601 J.P. Hennessy Drive
LaVergne, TN 37086-3565
800-688-6496 or 615-641-7533

Hennessy Canada

2430 Lucknow Drive, Unit #9
Mississauga, Ontario L5S 1V3
905-672-9440 Printed in USA.

www.ammcoats.com

Part No. 941262S Rev.2 11/01

MODEL NUMBER LEGEND

